



ENQUIRY

3 AXLE LOCOMOTIVE – WHD 600 66

TECHNICAL DATA:

MODEL : WHD 600 66
 SERVICE : SHUNTING
 RAIL GAUGE : 1676 mm
 AXLE CLASSIFICATION : O – C – O
 OVER ALL DIMENSIONS (mm) : L=8800, W=3100, H=4100
 NOMINAL AXLE LOAD (±3%) : 22.5 t
 ADHESIVE/TOTAL WEIGHT : 66 t
 TRACTIVE EFFORT AT START : 19800 kg.
 MAXIMUM GEARED SPEED : 18.8 KMPH
 WHEEL DIAMETER : 914 mm
 FUEL TANK CAPACITY : 1000 Lit PER LOCO
 INSTALLED POWER : 600hp (448kW)
 TRANSMISSION : HYDRODYNAMIC TURBO REVERSING



LOAD THAT CAN BE STARTED AND HAULED (IN TONNES)

TRACK CONDITION	SPEED				
	Starting	MCRS 5.6 Km/hr	10 Km/hr	15 Km/hr	18.8 Km/hr
Level	3800	3800	3800	2536	1696
1 IN 400 GRADIENT	2512	2512	2115	1235	815
8° CURVE	2292	2288	1847	1075	706

Admin & Works : Plot no. 23B, Industrial Park, Phase I, Patancheru-502 319, Hyderabad, Telangana, INDIA.
Phone : +91-8455-240670, 200026, 240563
Website : <http://ventralocomotives.com/>
Fax : +91-8455-241128
E-mail : hyd2_ventra@bsnl.in